

Bus-bar type

Current transformers with secondary current $I_{sn} = 20 \text{ mA}$ bus-bar type

ISN 1m

Type	Model/ Dimensions	Primary current	Rated parameters secondary curciut	
			burden	class
ISN 1m	h 021 $h_1 = 20,5 \text{ mm}$ $h_2 = 10,5 \text{ mm}$	50 A	50 Ω	1
			100 Ω	
			250 Ω	
		75 A	500 Ω	3
			750 Ω	
			50 Ω	
		100 Ω		
		250 Ω		
		100 A	500 Ω	0,5
			750 Ω	
			50 Ω	
		100 Ω		
250 Ω				
150 A	500 Ω	0,5		
	750 Ω			
	50 Ω		1	
100 Ω				
250 Ω				
200 ÷ 500 A	500 Ω	0,5		
	750 Ω			
	50 Ω		3	
50 A 75 A	100 Ω	1		
	250 Ω			
	500 Ω			
100 ÷ 300 A	750 Ω	0,5		
	50 Ω		1	
	100 Ω			
400 A	250 Ω	0,5		
	500 Ω			
	750 Ω			
500 A	50 Ω	1		
	100 Ω			
	250 Ω			
600 ÷ 800 A	500 Ω	0,5		
	750 Ω			
	50 Ω		1	
100 Ω				
250 Ω				
500 Ω				
750 Ω				

