

ISN 2m

Type	Model/ Dimensions	Primary current	Rated parameters secondary curcuit		
			burden	class	
ISN 2m	h 041 h ₁ = 40,5 mm h ₂ = 10,5 mm	100 ÷ 150 A	50 Ω	1	
			100 Ω		
			250 Ω		
			500 Ω		
			750 Ω		
		200 ÷ 300 A	50 Ω	0,5	
			100 Ω		
			250 Ω		
		400 ÷ 1200 A	500 Ω	1	
750 Ω					
50 Ω	0,5				
100 Ω					
250 Ω					
ISN 2m	h 051 h ₁ = 50,5 mm h ₂ = 10,5 mm	100 A	50 Ω	1	
			100 Ω		
			250 Ω		3
			500 Ω		
		150 A	750 Ω	1	
			50 Ω		
			100 Ω		
			250 Ω		
		200 ÷ 250 A	500 Ω	0,5	
			750 Ω		
			50 Ω		1
			250 Ω		
		300 A	500 Ω	0,5	
			750 Ω		
			50 Ω		1
			250 Ω		
		400 ÷ 1000 A	50 Ω	0,5	
			100 Ω		
250 Ω					
750 Ω					
ISN 2m	h 061 h ₁ = 60,5 mm h ₂ = 10,5 mm	100 A	50 Ω	1	
			100 Ω		
			250 Ω		3
			500 Ω		
		150 ÷ 250 A	750 Ω	1	
			50 Ω		
			100 Ω		
			250 Ω		
		300 A	500 Ω	0,5	
			750 Ω		
			50 Ω		1
			250 Ω		
		400 A	500 Ω	0,5	
			750 Ω		
			50 Ω		1
			250 Ω		
		500 ÷ 1250 A	50 Ω	0,5	
			100 Ω		
250 Ω					
750 Ω					

