



IUSN 3

Type	Model/ Dimensions	Primary current	Rated parameters of secondary circuit		
			voltage	burden \geq	class
IUSN 3	h 061 h ₁ = 60.5 mm h ₂ = 10.5 mm	400 ÷ 1250 A	1 V 2 V 5 V	5000 Ω 10 000 Ω 25 000 Ω	1
	h 081 h ₁ = 80.5 mm h ₂ = 10.5 mm	500 ÷ 2000 A	10 V 15 V	50 000 Ω 75 000 Ω	



Type	Model/ Dimensions	Primary current	Rated parameters of secondary circuit		
			voltage	burden \geq	class
IUSN 30	h 041 h ₁ = 10.5 mm h ₂ = 42 mm C = 60 mm	300 ÷ 1250 A			
	h 051 h ₁ = 10.5 mm h ₂ = 52 mm C = 55 mm	300 ÷ 1250 A			
	h 061 h ₁ = 10.5 mm h ₂ = 62 mm C = 50 mm	300 ÷ 1600 A	1 V 2 V 5 V	5000 Ω 10 000 Ω 25 000 Ω	1
	h 043 h ₁ = 33 mm h ₂ = 42 mm C = 60 mm	300 ÷ 1600 A	10 V 15 V	50 000 Ω 75 000 Ω	
	h 053 h ₁ = 33 mm h ₂ = 52 mm C = 55 mm	300 ÷ 1600 A			
	h 063 h ₁ = 33 mm h ₂ = 62 mm C = 50 mm	400 ÷ 2000 A			



IUSN 30